

Floodlight LED 10 W rechargeable AU/NZ



Benefits

- Long independent operating time for extended jobs.
- Compact design for minimal overall dimensions.
- Adjustable magnetic clamp compatible with tripod.

Norms

☑ IP 54

GENERAL INFORMATION

Description

Rechargeable 10 W LED spotlight

Technical details

Power : 10 W.

Luminous flux : 1100 lm (Mode : 100 %) or 400 lm (Mode : 50 %).

Colour temperature : 6000 K.

Colour rendering index : 80.

Beam angle : 120°.

Resistance to 1 m height drop.

Material : Aluminium and rubber.

Clamp adjustable to 180°.

Magnetic clamp compatible with tripod.

Independent operating time 3 h (mode : 100 %) or 6 h (mode : 50 %).

Charge time : 6 h.

Charge indicator.

Battery Lithium 3.7 V / 4400 mAh.

Charger input voltage : 100-240 V AC.

Charger output voltage : 5 V DC - 1 A.

Powerbank USB port.

Supplied with main charger and a connection cable length 1 meter.

Weight : 750 grams.

Advices

Fully charge and discharge the battery for better lifetime.

Application(s)

Temporary battery-powered site lighting.

Instructions



1. Button to choose the desired luminous flux (100 % - 50 % - Off). Operates when the device is connected to the mains.

 LOGISTIC INFORMATION

 Packaging



Carton box



Height (cm) : 23,5
 Length (cm) : 19,5
 Depth (cm) : 5,5
 Net weight (kg) : 0,855
 Gross weight (kg) : 0,925



 Outer package 1



Carton box

Height (cm) : 40
 Length (cm) : 18
 Depth (cm) : 24
 Net weight (kg) : 5,5
 Gross weight (kg) : 5,7





x 6.00

 Outer package 2



Carton box

Height (cm) : 41,5
 Length (cm) : 25,5
 Depth (cm) : 38
 Net weight (kg) : 11
 Gross weight (kg) : 12





x 12.00

 Outer package 3



Pallet

Height (cm) : 100
 Length (cm) : 120
 Depth (cm) : 80
 Net weight (kg) : 252
 Gross weight (kg) : 267



x 252.00